PREDICTED ENERGY ASSESSMENT



139, Stafford Road, Wolverhampton, WV10 6AJ Dwelling type: House, Detached

Date of assessment: 03/06/2021
Produced by: David Moses
Total floor area: 89.28 m²

DRRN: 0667-2606-0090

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO₂) emissions.

Very energy efficient - lower running costs (92 plus) A (81-91) B (69-80) C (55-68) D (39-54) E (21-38) F (1-20) G Not energy efficient - higher running costs Eu Directive 2002/91/EC

The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

Environmental Impact (CO₂) Rating Very environmentally friendly - lower CO₂ emissions (92 plus) A (81-91) B (69-80) C (55-68) D (39-54) E (21-38) F (1-20) Not environmentally friendly - higher CO₂ emissions England EU Directive 2002/91/EC

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO₂) emissions. The higher the rating the less impact it has on the environment.





BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



kWh/m²/yr

Pass

Property Reference	e Plot 139 Goodyear			Issued on Date 03/06/20			
Assessment Reference	1			Prop Type Ref			
Property	139, Stafford Road, Wolv	, Stafford Road, Wolverhampton, WV10 6AJ					
SAP Rating		83 B	DER	18.42	TER	19.26	
Environmental		85 B	% DER <ter< th=""><th></th><th colspan="3">4.35</th></ter<>		4.35		
CO ₂ Emissions (t/y	ear)	1.45	DFEE	50.93	50.93 TFEE 58.46		
General Requirem	ents Compliance	Pass	% DFEE <tfe< th=""><th>E</th><th colspan="2">12.88</th></tfe<>	E	12.88		
Assessor Details	Mr. David Moses, David Mos	es, Tel: 01216	330000, david	m@bm3.co.uk	bm3.co.uk Assessor ID T612-0001		
Client	St Modwen Homes						
SLIMARY FOR INPLIT DATA FOR New Build (As Designed)							

SUMARY FOR INPUT DATA FOR New Build (As Designed

Criterion 1 – Achieving the TER and TFEE rate

1a TER and DER

Fuel for main heating	Mains gas		
Fuel factor	1.00 (mains gas)		
Target Carbon Dioxide Emission Rate (TER)	19.26	kgCO ₂ /m ²	
Dwelling Carbon Dioxide Emission Rate (DER)	18.42	kgCO ₂ /m ²	Pass
	-0.84 (-4.4%)	kgCO ₂ /m ²	
1b TFEE and DFEE			
Target Fabric Energy Efficiency (TFEE)	58.46	kWh/m²/yr	
Dwelling Fabric Energy Efficiency (DFEE)	50.93	kWh/m²/yr	

-7.6 (-13.0%)

Criterion 2 – Limits on design flexibility

Limiting Fabric Standards

2 Fabric U-values

Element	Average	Highest	
External wall	0.21 (max. 0.30)	0.21 (max. 0.70)	Pass
Floor	0.15 (max. 0.25)	0.15 (max. 0.70)	Pass
Roof	0.10 (max. 0.20)	0.10 (max. 0.35)	Pass
Openings	1.32 (max. 2.00)	1.37 (max. 3.30)	Pass

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals	5.00 (design value)	m³/(h.m²) @ 50 Pa	
Maximum	10.0	m³/(h.m²) @ 50 Pa	Pass

Limiting System Efficiencies

4 Heating efficiency





BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Main heating system Boiler system with radiators or underfloor - Mains gas			ISS
	Data from database		
	Ideal LOGIC COMBI ESP1 30		
	Combi boiler		
	Efficiency: 89.6% SEDBUK2009		
Cocondany booting system	Minimum: 88.0%		1
Secondary heating system	None		
5 Cylinder insulation	D		
Hot water storage	No cylinder		
<u>6 Controls</u>			
Space heating controls	Time and temperature zone control	Pa	ISS
Hot water controls	No cylinder		
Boiler interlock	Yes	Pa	ISS
7 Low energy lights			
Percentage of fixed lights with low-energy fittings	100	%	
Minimum	75	% Pa	ISS
8 Mechanical ventilation			
Not applicable			
Criterion 3 – Limiting the effects of heat gains in sur	mmer		
9 Summertime temperature			
Overheating risk (Midlands)	Not significant	Pa	ISS
Based on:	-		
Overshading	Average		
Windows facing North East	3.67 m ² , No overhang		
Windows facing South East	1.09 m ² , Overhang width less than twice windo		
Windows facing South West	2.88 m ² , Overhang width less than twice windo	w, ratio 0.01	
Windows facing North West	4.19 m ² , No overhang		
Air change rate	8.00 ach		
Blinds/curtains	None		
Criterion 4 – Building performance consistent with	DER and DFEE rate		
Air permeability and pressure testing			
3 Air permeability			
Air permeability at 50 pascals	5.00 (design value) m ³ /(h.	m²) @ 50 Pa	
Maximum	10.0 m ³ /(h.	m²) @ 50 Pa Pa	ISS
10 Key features			
Roof U-value	0.10	N/m²K	
Door U-value	1.10	N/m²K	
Thermal bridging y-value	0.031	N/m²K	





RECOMMENDATIONS



	Typical cost	Typical savings per year	Energy efficiency	Environmental impact	Result
Low energy lights			0	0	Already installed
Solar water heating	£4,000 - £6,000	£28	B 85	B 87	Recommended
Photovoltaic	£3,500 - £5,500	£336	A 95	A 96	Recommended
Wind turbine			0	0	Not applicable
Totals	£7,500 - £11,500	£365	A 95	A 96	



