PREDICTED ENERGY ASSESSMENT



Plot 087, Rogerson Gardens, Dwelling type: House, End-Terrace

Preston, Date of assessment: 29/04/2022
PR3 Produced by: Hazel Black
Total floor area: 86.02 m²

DRRN: 9222-1241-1051

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO₂) emissions.

Very energy efficient - lower running costs (92 plus) A (81-91) B (69-80) C (55-68) D (39-54) E (21-38) F (1-20) G Not energy efficient - higher running costs England EU Directive 2002/91/EC

The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

Very environmental Impact (CO₂) Rating Very environmentally friendly - lower CO₂ emissions (92 plus) A (81-91) B (69-80) C (55-68) D (39-54) E (1-20) G Not environmentally friendly - higher CO₂ emissions EU Directive 2002/91/EC

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO₂) emissions. The higher the rating the less impact it has on the environment.





BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Property Reference	Plot 087 T52 ET			Issued on Date	29/04/2022			
Assessment	1 Prop Type Ref			rop Type Ref				
Reference								
Property	Plot 087, Rogerson Garde	ns, Preston, P	R3					
SAP Rating		84 B	DER	17.21	TER	17.92		
Environmental		86 B	% DER <ter< th=""><td></td><td colspan="2">3.96</td></ter<>		3.96			
CO ₂ Emissions (t/year)		1.34	DFEE	46.85	TFEE	49.93		
General Requirements	General Requirements Compliance		% DFEE <tfee< th=""><td></td><td colspan="2">6.17</td></tfee<>		6.17			
Assessor Details Ms	s. Hazel Black, Hazel Black, ¹	Tel: 01582 544	4250, hazelb@ee	-ltd.co.uk	Assessor ID	M003-0001		
Client								
SUMARY FOR INPUT DATA FOR New Build (As Designed)								
Criterion 1 – Achieving	· · · · · · · · · · · · · · · · · · ·	<u>. </u>						
1a TER and DER								
Fuel for main heating	σ	Mains ga	ıs					
Fuel factor	_		1.00 (mains gas)					
Target Carbon Dioxide Emission Rate (TER)			17.92			kgCO ₂ /m ²		
Dwelling Carbon Dioxide Emission Rate (DER)		17.21		kgCO ₂ /m ²	Pass			
			-0.71 (-4.0%)			kgCO ₂ /m²		
1b TFEE and DFEE		,	,					
Target Fabric Energy Efficiency (TFEE)		49.93		kWh/m²/yr				
Dwelling Fabric Energy Efficiency (DFEE)		46.85	46.85			kWh/m²/yr		
		-3.0 (-6.0	-3.0 (-6.0%)			Pass		
Criterion 2 – Limits on d	lesign flexibility							
Limiting Fabric Stand	dards							

Limiting Fabric Standards

2 Fabric U-values

Element	Average	Highest	
External wall	0.27 (max. 0.30)	0.27 (max. 0.70)	Pass
Party wall	0.00 (max. 0.20)	-	Pass
Floor	0.15 (max. 0.25)	0.15 (max. 0.70)	Pass
Roof	0.11 (max. 0.20)	0.11 (max. 0.35)	Pass
Openings	1.29 (max. 2.00)	1.41 (max. 3.30)	Pass

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals	5.01 (design value)	m³/(h.m²) @ 50 Pa	
Maximum	10.0	m³/(h.m²) @ 50 Pa	Pass

Limiting System Efficiencies

4 Heating efficiency





BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Main heating system	Boiler system with radiators or underfloor - Mains gas Data from database	Pass		
	Ideal LOGIC COMBI ESP1 35			
	Combi boiler			
	Efficiency: 89.6% SEDBUK2009			
	Minimum: 88.0%			
Secondary heating system	None			
5 Cylinder insulation				
Hot water storage	No cylinder			
<u>6 Controls</u>				
Space heating controls	Time and temperature zone control	Pass		
Hot water controls	No cylinder			
Boiler interlock	Yes	Pass		
7 Low energy lights				
Percentage of fixed lights with low-energy fittings	100 %			
Minimum	75 %	Pass		
8 Mechanical ventilation				
Not applicable				
Criterion 3 – Limiting the effects of heat gains in su	mmer			
9 Summertime temperature				
Overheating risk (West Pennines (England))	Not significant	Pass		
Based on:				
Overshading	Average			
Windows facing North East	4.10 m ² , No overhang			
Windows facing South East	1.32 m ² , No overhang			
Windows facing South West	4.89 m², No overhang			
Air change rate	4.00 ach			
Blinds/curtains	Dark-coloured curtain or roller blind, closed 100% of dayli	ght		
	hours			
Criterion 4 – Building performance consistent with	DER and DFEE rate			
Party Walls				
Туре	U-value			
Filled Cavity with Edge Sealing	0.00 W/m²K	Pass		
Air permeability and pressure testing				
3 Air permeability				
Air permeability at 50 pascals 5.01 (design value) m³/(h.m²) @ 5				
Maximum	10.0 m ³ /(h.m ²) @ 50 P	a Pass		
10 Key features				
Party wall U-value	0.00 W/m ² K			
Roof U-value	0.11 W/m²K			
Door U-value	1.00 W/m²K			





RECOMMENDATIONS



	Typical cost	Typical savings per year	Energy efficiency	Environmental impact	Result
Low energy lights			0	0	Already installed
Solar water heating	£4,000 - £6,000	£25	B 85	B 88	Recommended
Photovoltaic	£3,500 - £5,500	£332	A 95	A 97	Recommended
Wind turbine			0	0	Not applicable
Totals	£7,500 - £11,500	£357	A 95	A 97	



