PREDICTED ENERGY ASSESSMENT



Plot 153, Rogerson Gardens, Dwelling type: House, Mid-Terrace

Preston, Date of assessment: 29/04/2022
PR3 Produced by: Hazel Black
Total floor area: 86.02 m²

DRRN: 9002-0461-2253

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP2012 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO₂) emissions.

Very energy efficient - lower running costs (92 plus) A (81-91) B (69-80) C (55-68) D (39-54) E (1-20) G Not energy efficient - higher running costs England EU Directive 2002/91/EC

The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

Environmental Impact (CO₂) Rating Very environmentally friendly - lower CO₂ emissions (92 plus) A (81-91) B (69-80) C (55-68) D (39-54) E (21-38) F (1-20) Not environmentally friendly - higher CO₂ emissions England EU Directive 2002/91/EC

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO₂) emissions. The higher the rating the less impact it has on the environment.





BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



kWh/m²/yr

kWh/m²/yr

Pass

Property Reference Plot 153 T52 MT	Plot 153 T52 MT				29/04/2022
Assessment 1 Reference	1 Prop Type Ref				
Property Plot 153, Rogerson Gardens, Preston, PR3					
SAP Rating	85 B	DER	15.08	TER	16.57
Environmental	88 B	% DER <ter< th=""><th colspan="3">8.98</th></ter<>	8.98		
CO ₂ Emissions (t/year)	1.17	DFEE	37.03 TFEE 42.42		42.42
General Requirements Compliance	Pass	% DFEE <tfee< th=""><th colspan="3">12.70</th></tfee<>	12.70		
Assessor Details Ms. Hazel Black, Hazel Black, Tel: 01582 544250, hazelb@ee-ltd.co.uk Assessor ID M003-0001 Client					

SUMARY FOR INPUT DATA FOR New Build (As Designed)

Criterion 1 – Achieving the TER and TFEE rate

1a TER and DER

Fuel for main heating	Mains gas		
Fuel factor	1.00 (mains gas)		
Target Carbon Dioxide Emission Rate (TER)	16.57	kgCO ₂ /m ²	
Dwelling Carbon Dioxide Emission Rate (DER)	15.08	kgCO ₂ /m ²	Pass
	-1.49 (-9.0%)	kgCO ₂ /m ²	
1b TFEE and DFEE			
Target Fabric Energy Efficiency (TFEE)	42.42	kWh/m²/yr	

37.03

-5.4 (-12.7%)

Criterion 2 – Limits on design flexibility

Dwelling Fabric Energy Efficiency (DFEE)

Limiting Fabric Standards

2 Fabric U-values

Element	Average	Highest	
External wall	0.27 (max. 0.30)	0.27 (max. 0.70)	Pass
Party wall	0.00 (max. 0.20)	-	Pass
Floor	0.13 (max. 0.25)	0.13 (max. 0.70)	Pass
Roof	0.11 (max. 0.20)	0.11 (max. 0.35)	Pass
Openings	1.28 (max. 2.00)	1.41 (max. 3.30)	Pass

2a Thermal bridging

Thermal bridging calculated from linear thermal transmittances for each junction

3 Air permeability

Air permeability at 50 pascals	5.01 (design value)	m³/(h.m²) @ 50 Pa	
Maximum	10.0	m³/(h.m²) @ 50 Pa	Pass

Limiting System Efficiencies

4 Heating efficiency





BUILDING REGULATION COMPLIANCE Calculation Type: New Build (As Designed)



Main heating system	stem Boiler system with radiators or underfloor - Mains gas		
	Data from database		
	Ideal LOGIC COMBI ESP1 35		
	Combi boiler		
	Efficiency: 89.6% SEDBUK2009		
	Minimum: 88.0%		
Secondary heating system	None		
5 Cylinder insulation			
Hot water storage	No cylinder		
<u>6 Controls</u>			
Space heating controls	Time and temperature zone control		Pass
Hot water controls	No cylinder		
Boiler interlock	Yes		Pass
7 Low energy lights			
Percentage of fixed lights with low-energy	100	%	
fittings			
Minimum	75	%	Pass
8 Mechanical ventilation			
Not applicable			
Criterion 3 – Limiting the effects of heat gains in su	mmer		
9 Summertime temperature			
Overheating risk (West Pennines (England))	Not significant		Pass
Based on:			
Overshading	Average		
Windows facing East	4.89 m², No overhang		
Windows facing West	4.10 m ² , No overhang		
Air change rate	4.00 ach		
Blinds/curtains	Dark-coloured curtain or roller blind, closed 100% of daylight		
	hours		
Criterion 4 – Building performance consistent with	DER and DFEE rate		
Party Walls			
Туре	U-value		
Filled Cavity with Edge Sealing	0.00	W/m²K	Pass
Air permeability and pressure testing			
3 Air permeability			
Air permeability at 50 pascals	5.01 (design value) m ³ /(l	h.m²) @ 50 Pa	
Maximum	10.0 m³/(l	h.m²) @ 50 Pa	Pass
10 Key features			
Party wall U-value	0.00	W/m²K	
Roof U-value	0.11	W/m²K	
Door U-value	1.00	W/m²K	





RECOMMENDATIONS



	Typical cost	Typical savings per year	Energy efficiency	Environmental impact	Result
Low energy lights			0	0	Already installed
Solar water heating	£4,000 - £6,000	£25	B 86	B 90	Recommended
Photovoltaic	£3,500 - £5,500	£332	A 97	A 99	Recommended
Wind turbine			0	0	Not applicable
Totals	£7,500 - £11,500	£357	A 97	A 99	



