

# Building Regulations England Part L (BREL) Compliance Report

Approved Document L1 2021 Edition, England assessed by Array SAP 10 program, Array

Date: Mon 10 Jun 2024 09:25:46

Project Information			
Assessed By	Demi Beneke	Building Type	House, Mid-terrace
OCDEA Registration	EES/027264	Assessment Date	2024-06-10

Dwelling Details			
Assessment Type	As designed	Total Floor Area	84 m <sup>2</sup>
Site Reference	Plot 24	Plot Reference	Plot 24
Address			

Client Details	
Name	AJC
Company	AJC
Address	4 Joshuas Vista, Poole, BH14 8HA

This report covers items included within the SAP calculations. It is not a complete report of regulations compliance.

## 1a Target emission rate and dwelling emission rate

Fuel for main heating system	Electricity
Target carbon dioxide emission rate	9.86 kgCO <sub>2</sub> /m <sup>2</sup>
Dwelling carbon dioxide emission rate	4.2 kgCO <sub>2</sub> /m <sup>2</sup> OK

## 1b Target primary energy rate and dwelling primary energy

Target primary energy	51.26 kWh <sub>PE</sub> /m <sup>2</sup>
Dwelling primary energy	43.91 kWh <sub>PE</sub> /m <sup>2</sup> OK

## 1c Target fabric energy efficiency and dwelling fabric energy efficiency

Target fabric energy efficiency	30.7 kWh/m <sup>2</sup>
Dwelling fabric energy efficiency	27.4 kWh/m <sup>2</sup> OK

## 2a Fabric U-values

Element	Maximum permitted average U-Value [W/m <sup>2</sup> K]	Dwelling average U-Value [W/m <sup>2</sup> K]	Element with highest individual U-Value	
External walls	0.26	0.18	Walls (1) (0.18)	OK
Party walls	0.2	0	Party Wall (1) (0)	N/A
Curtain walls	1.6	0	N/A	N/A
Floors	0.18	0.11	Ground Floor (0.11)	OK
Roofs	0.16	0.11	Roof (1) (0.11)	OK
Windows, doors, and roof windows	1.6	1.29	W1 (1.3)	OK
Rooflights	2.2	N/A	N/A	N/A

## 2b Envelope elements (better than typically expected values are flagged with a subsequent (!))

Name	Net area [m <sup>2</sup> ]	U-Value [W/m <sup>2</sup> K]
Exposed wall: Walls (1)	35.029225	0.18
Party wall: Party Wall (1)	86.12	0 (!)
Ground floor: Ground Floor, Ground Floor	42.05	0.11
Exposed roof: Roof (1)	42.05	0.11

## 2c Openings (better than typically expected values are flagged with a subsequent (!))

Name	Area [m <sup>2</sup> ]	Orientation	Frame factor	U-Value [W/m <sup>2</sup> K]
D1, Door	2.15853	North East	N/A	1.2
W1, Windows	0.2806	North East	1.0	1.3
W2, Windows	2.32585	North East	1.0	1.3
W6, Windows	0.7261	South West	1.0	1.3
W7, Windows	4.29385	South West	1.0	1.3
W8, Windows	3.193225	North East	1.0	1.3
W10, Windows	1.602395	South West	1.0	1.3
W11, Windows	0.880225	South West	1.0	1.3

## 2d Thermal bridging (better than typically expected values are flagged with a subsequent (!))

Building part 1 - Main Dwelling: Thermal bridging calculated from linear thermal transmittances for each junction

Main element	Junction detail	Source	Psi value [W/mK]	Drawing / reference
External wall	E2: Other lintels (including other steel lintels)	Calculated by person with suitable expertise	0.02 (!)	RCD
External wall	E3: Sill	Calculated by person with suitable expertise	0.023 (!)	RCD
External wall	E4: Jamb	Calculated by person with suitable expertise	0.018 (!)	RCD
External wall	E5: Ground floor (normal)	Calculated by person with suitable expertise	0.031 (!)	K
External wall	E6: Intermediate floor within a dwelling	Calculated by person with suitable expertise	0.001 (!)	
External wall	E10: Eaves (insulation at ceiling level)	Calculated by person with suitable expertise	0.055	RCD
External wall	E18: Party wall between dwellings	Calculated by person with suitable expertise	0.029 (!)	K
Party wall	P1: Ground floor	Calculated by person with suitable expertise	0.043	- RCD
Party wall	P2: Intermediate floor within a dwelling	SAP table default	0 (!)	
Party wall	P4: Roof (insulation at ceiling level)	Calculated by person with suitable expertise	0.033 (!)	RCD

### 3 Air permeability (better than typically expected values are flagged with a subsequent (!))

Maximum permitted air permeability at 50Pa	8 m <sup>3</sup> /hm <sup>2</sup>	
Dwelling air permeability at 50Pa	5 m <sup>3</sup> /hm <sup>2</sup> , Design value	OK
Air permeability test certificate reference		

### 4 Space heating

#### Main heating system 1: Room heaters - Electricity

Efficiency	100.0%
Emitter type	
Flow temperature	
System type	Panel, convector or radiant heaters
Manufacturer	
Model	
Commissioning	

#### Main heating system 2: Heat pump with radiators or underfloor heating - Electricity

Efficiency	0.0%
Emitter type	
Flow temperature	
System type	Heat Pump
Manufacturer	GDC Group Ltd
Model	EDL200UK-630
Commissioning	

#### Secondary heating system: N/A

Fuel	N/A
Efficiency	N/A
Commissioning	

### 5 Hot water

#### Cylinder/store - type: N/A

Capacity	N/A
Declared heat loss	N/A
Primary pipework insulated	N/A
Manufacturer	
Model	
Commissioning	

#### Waste water heat recovery system 1 - type: Instantaneous

Efficiency	65.0%
Manufacturer	Q-Blue B.V.
Model	QB1-21

<b>6 Controls</b>		
<b>Main heating 1</b> - type: Programmer and appliance thermostats		
Function		
Ecodesign class		
Manufacturer		
Model		
<b>Main heating 2</b> - type: Not applicable		
Function		
Ecodesign class		
Manufacturer		
Model		
<b>Water heating</b> - type: N/A		
Manufacturer		
Model		
<b>7 Lighting</b>		
Minimum permitted light source efficacy	75 lm/W	
Lowest light source efficacy	80 lm/W	OK
External lights control	N/A	
<b>8 Mechanical ventilation</b>		
<b>System type:</b> N/A		
Maximum permitted specific fan power	N/A	
Specific fan power	N/A	N/A
Minimum permitted heat recovery efficiency	N/A	
Heat recovery efficiency	N/A	N/A
Manufacturer/Model		
Commissioning		
<b>9 Local generation</b>		
Technology type: <b>Photovoltaic system (1)</b>		
Peak power	0.5 kWp	
Orientation	South West	
Pitch	45°	
Overshading	None or very little	
Manufacturer		
MCS certificate		
<b>10 Heat networks</b>		
N/A		
<b>11 Supporting documentary evidence</b>		
N/A		
<b>12 Declarations</b>		
<b>a. Assessor Declaration</b>		
This declaration by the assessor is confirmation that the contents of this BREL Compliance Report are a true and accurate reflection based upon the design information submitted for this dwelling for the purpose of carrying out the "As designed" assessment, and that the supporting documentary evidence (SAP Conventions, Appendix 1 (documentary evidence) schedules the minimum documentary evidence required) has been reviewed in the course of preparing this BREL Compliance Report.		
Signed:	Assessor ID:	
Name:	Date:	
<b>b. Client Declaration</b>		
N/A		

# Summary for Input Data

Property Reference	Plot 24	Issued on Date	10/06/2024
Assessment Reference	Plot 24	Prop Type Ref	
Property			

SAP Rating	84 B	DER	4.20	TER	9.86
Environmental	97 A	% DER < TER			57.40
CO <sub>2</sub> Emissions (t/year)	0.27	DFEE	27.38	TFEE	30.70
Compliance Check	See BREL	% DFEE < TFEE			10.84
% DPER < TPER	14.34	DPER	43.91	TPER	51.26

Assessor Details	Ms. Demi Beneke	Assessor ID	AV37-0001
Client			

## SUMMARY FOR INPUT DATA FOR: New Build (As Designed)

Orientation	Northeast	
Property Tenture	ND	
Transaction Type	6	
Terrain Type	Suburban	
1.0 Property Type	House, Mid-Terrace	
Which Floor	0	
2.0 Number of Storeys	2	
3.0 Date Built	2024	
3.0 Property Age Band	L	
4.0 Sheltered Sides	2	
5.0 Sunlight/Shade	Average or unknown	
6.0 Thermal Mass Parameter	Precise calculation	
Thermal Mass	N/A	kJ/m²K
7.0 Electricity Tariff	Standard	
Smart electricity meter fitted	Yes	
Smart gas meter fitted	Yes	

7.0 Measurements	Heat Loss Perimeter	Internal Floor Area	Average Storey Height
Basement:	0.00 m	0.00 m <sup>2</sup>	0.00 m
Ground floor:	9.92 m	42.05 m <sup>2</sup>	2.42 m
1st Storey:	9.92 m	42.05 m <sup>2</sup>	2.67 m
2nd Storey:	0.00 m	0.00 m <sup>2</sup>	0.00 m
3rd Storey:	0.00 m	0.00 m <sup>2</sup>	0.00 m
4th Storey:	0.00 m	0.00 m <sup>2</sup>	0.00 m
5th Storey:	0.00 m	0.00 m <sup>2</sup>	0.00 m
6th Storey:	0.00 m	0.00 m <sup>2</sup>	0.00 m
7th Storey:	0.00 m	0.00 m <sup>2</sup>	0.00 m

8.0 Living Area	16.44	m <sup>2</sup>
-----------------	-------	----------------

9.0 External Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area (m <sup>2</sup> )	Shelter Res	Shelter	Openings	Area Calculation Type
	External Wall	Cavity Wall	Cavity wall : plasterboard on dabs, AAC block, filled cavity, any outside structure	0.18	60.00	50.49	35.03	0.00	None	15.46	Enter Gross Area

9.1 Party Walls	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )	Shelter Res	Shelter
	Party Wall	Filled Cavity with Edge Sealing	Single plasterboard on dabs on both sides, dense blocks, cavity or cavity fill	0.00	70.00	86.12	0.00	None

9.2 Internal Walls	Description	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
	Internal Wall	Plasterboard on timber frame	9.00	164.99

10.0 External Roofs	Description	Type	Construction	U-Value (W/m <sup>2</sup> K)	Kappa (kJ/m <sup>2</sup> K)	Gross Area(m <sup>2</sup> )	Nett Area	Shelter Code	Shelter Factor	Calculation Type	Openings
---------------------	-------------	------	--------------	------------------------------	-----------------------------	-----------------------------	-----------	--------------	----------------	------------------	----------

# Summary for Input Data

Plain Ceiling	External Plane Roof	Plasterboard, insulated at ceiling level	0.11	9.00	42.05	(m <sup>2</sup> ) 42.05	None	0.00	Enter Gross Area	0.00
---------------	---------------------	--	------	------	-------	----------------------------	------	------	------------------	------

## 10.2 Internal Ceilings

Description	Storey	Construction	Area (m <sup>2</sup> )
Internal Ceiling 1	Lowest occupied	Plasterboard ceiling, carpeted chipboard floor	42.05

## 11.0 Heat Loss Floors

Description	Type	Storey Index	Construction	U-Value (W/m <sup>2</sup> K)	Shelter Code	Shelter Factor	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Ground Floor	Ground Floor - Solid	Lowest occupied	Suspended concrete floor, carpeted	0.11	None	0.00	75.00	42.05

## 11.2 Internal Floors

Description	Storey Index	Construction	Kappa (kJ/m <sup>2</sup> K)	Area (m <sup>2</sup> )
Internal Floor 1		Plasterboard ceiling, carpeted chipboard floor	9.00	42.05

## 12.0 Opening Types

Description	Data Source	Type	Glazing	Glazing Gap	Filling Type	G-value	Frame Type	Frame Factor	U Value (W/m <sup>2</sup> K)
Door	Manufacturer	Solid Door			Air Filled	0.00	Wood	0.70	1.20
Windows	BFRC, BSI or CERTASS data	Window	Double Low-E Soft 0.05		Air Filled	0.45	Wood	1.00	1.30

## 13.0 Openings

Name	Opening Type	Location	Orientation	Area (m <sup>2</sup> )	Pitch
D1	Door	External Wall	North East	2.16	0
W1	Windows	External Wall	North East	0.28	0
W2	Windows	External Wall	North East	2.33	0
W6	Windows	External Wall	South West	0.73	0
W7	Windows	External Wall	South West	4.29	0
W8	Windows	External Wall	North East	3.19	0
W10	Windows	External Wall	South West	1.60	0
W11	Windows	External Wall	South West	0.88	0

## 14.0 Conservatory

None

## 15.0 Draught Proofing

100 %

## 16.0 Draught Lobby

No

## 17.0 Thermal Bridging

Calculate Bridges

## 17.1 List of Bridges

Bridge Type	Source Type	Length	Psi	Adjusted Reference:	Imported
E2 Other lintels (including other steel lintels)	Independently assessed	10.43	0.02	0.02 RCD	No
E3 Sill	Independently assessed	7.37	0.02	0.02 RCD	No
E4 Jamb	Independently assessed	22.06	0.02	0.02 RCD	No
E5 Ground floor (normal)	Independently assessed	9.92	0.03	0.03 K	No
E6 Intermediate floor within a dwelling	Independently assessed	9.92	0.00	0.00	No
E10 Eaves (insulation at ceiling level)	Independently assessed	9.92	0.06	0.06 RCD	No
E18 Party wall between dwellings	Independently assessed	20.36	0.03	0.03 K	No
P1 Party wall - Ground floor	Independently assessed	16.92	0.04	0.04 - RCD	No
P2 Party wall - Intermediate floor within a dwelling	Table K1 - Default	16.92	0.00	0.00	No
P4 Party wall - Roof (insulation at ceiling level)	Independently assessed	16.92	0.03	0.03 RCD	No

## Y-value

0.03 W/m<sup>2</sup>K

## 18.0 Pressure Testing

Yes

Designed AP<sub>50</sub>

5.00 m<sup>3</sup>/(h.m<sup>2</sup>) @ 50 Pa

Property Tested?

Yes

Test Method

Blower Door

## 19.0 Mechanical Ventilation

### Mechanical Ventilation

Mechanical Ventilation System Present

No

## 20.0 Fans, Open Fireplaces, Flues

## 21.0 Fixed Cooling System

No

## 22.0 Lighting

No Fixed Lighting

No

Name	Efficacy	Power	Capacity	Count
Lighting	80.00	25	2000	10

## 24.0 Main Heating 1

SAP table

Percentage of Heat

100.00 %



# Summary for Input Data

## 28.1 Showers

Description	Shower Type	Flow Rate [l/min]	Rated Power [kW]	Connected	Connected To
Bath	Combi boiler or unvented hot water system	10.00		Yes	Instantaneous System 1

## 28.3 Waste Water Heat Recovery System Instantaneous System 1

Database ID	80116
Brand Model	Showersave, QB1-21
Details	Year: 2017 + current Efficiency: 64.95 Utilisation factor: 0.973

## 29.0 Hot Water Cylinder

Cylinder Stat	Internal Store	
Cylinder In Heated Space	No	
Independent Time Control	No	
Insulation Type	Measured Loss	
Cylinder Volume	201.00	L
Loss	1.61	kWh/day
In Airing Cupboard	No	

## 31.0 Thermal Store

	None
--	------

## 32.0 Photovoltaic Unit

Export Capable Meter?	One Dwelling
Connected To Dwelling	Yes
Diverter	Yes
Battery Capacity [kWh]	No
	0.00

PV Cells kWp	Orientation	Elevation	Overshading	FGHRS	MCS Certificate	Overshading Factor	MCS Certificate Reference	Panel Manufacturer
0.50	South West	45°	None Or Little	No	No	1.00		

## 34.0 Small-scale Hydro

Electricity Generated	<div><div></div><div>0.00</div></div>								kWh/Year			
Apportioned	<div><div></div><div>0.00</div></div>											
Connected to dwelling's electricity meter	<div><div></div><div>Yes</div></div>											
Electricity Generation	<div><div></div><div>Annual</div></div>											
Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	

## Recommendations

### Lower cost measures

None

### Further measures to achieve even higher standards

None


# Predicted Energy Assessment



Dwelling type: House, Mid-Terrace  
Date of assessment: 10/06/2024  
Produced by: Demi Beneke  
Total floor area: 84.1 m<sup>2</sup>  
DRRN:

This document is a Predicted Energy Assessment for properties marketed when they are incomplete. It includes a predicted energy rating which might not represent the final energy rating of the property on completion. Once the property is completed, this rating will be updated and an official Energy Performance Certificate will be created for the property. This will include more detailed information about the energy performance of the completed property.

The energy performance has been assessed using the Government approved SAP 10 methodology and is rated in terms of the energy use per square meter of floor area; the energy efficiency is based on fuel costs and the environmental impact is based on carbon dioxide (CO<sub>2</sub>) emissions.



The energy efficiency rating is a measure of the overall efficiency of a home. The higher the rating the more energy efficient the home is and the lower the fuel bills are likely to be.

The environmental impact rating is a measure of a home's impact on the environment in terms of carbon dioxide (CO<sub>2</sub>) emissions. The higher the rating the less impact it has on the environment.